

# MT100 Specs & Compare

## ▲ MT100 Key Specifications

### MT100

Rated Operating Capacity with Bucket (Straight)	1000 lbs
Operating Weight	3390 lbs
Auxiliary Std Flow	11 gpm
Width	35.6 in
Height to Bucket Hinge Pin	80.9 in

## ▼ Engine

### MT100

Horsepower	24.8 hp
Displacement	55 cubic in

## ▼ Performance

### MT100

Ground Pressure (Optional Tracks)	4 psi
Ground Pressure (Standard Tracks)	5.3 psi
Rated Operating Capacity with Bucket (Straight)	1000 lbs
Tipping Load	2898 lbs
Operating Weight	3390 lbs

Travel Speed - Forward	4.1 mph
Travel Speed - Reverse	2.9 mph
Travel Speed - Low	4.1 mph
Travel Speed - High	4.1 mph

#### ▼ Hydraulic System

**MT100**

System Relief @ Quick Couplers	2900 psi
Auxiliary Std Flow	11 gpm

#### ▼ Dimensions

**MT100**

Width	35.6 in
Height to Bucket Hinge Pin	80.9 in
Reach @ Maximum Height	18.6 in
Track Width - Wide	9.8 in
Track Width - Standard	7.1 in

#### ▼ Features

**MT100**

Bob-Tach Attachment System	Optional
Common Industry Interface	Optional