

# T64 Specifications

▲ **T64 Key Specifications**

T64

Horsepower	<b>68 hp</b>
ROC Solid Undercarriage	<b>2300 lbs</b>
Rated Operating Capacity	<b>2300 lbs</b>
Operating Weight	<b>8440 lbs</b>
Travel Speed (1-Speed)	<b>7.2 mph</b>
Travel Speed - Low (2-Speed)	<b>7.2 mph</b>
Travel Speed - High (2-Speed)	<b>10.2 mph</b>
Auxiliary Std Flow	<b>17.6 gpm</b>
Auxiliary High Flow	<b>26.9 gpm</b>
Length without Attachment	<b>107 in</b>
Overall Width	<b>67.8 in</b>
Overall Height	<b>80.5 in</b>
Height to Hinge Pin	<b>120 in</b>
Reach @ Maximum Height	<b>36.7 in</b>

▼ **Engine**

T64

Horsepower	<b>68 hp</b>
Alternator	<b>90 A</b>
Battery Size	<b>1000 CCA</b>
Engine-High Idle	<b>2600 RPM</b>
Engine-Low Idle	<b>1050 RPM</b>
Air Cleaner Elements	<b>REPLACEABLE DRY PAPER CARTRIDGE WITH SEPARATE SAFETY ELEMENT</b>

### ▼ Performance

	<b>T64</b>
Rated Operating Capacity 200 lb. Counterweight	<b>2450 lbs</b>
ROC Solid Undercarriage	<b>2300 lbs</b>
Rated Operating Capacity	<b>2300 lbs</b>
Tipping Load	<b>6793 lbs</b>
Operating Weight	<b>8440 lbs</b>
Travel Speed (1-Speed)	<b>7.2 mph</b>
Travel Speed - Low (2-Speed)	<b>7.2 mph</b>
Travel Speed - High (2-Speed)	<b>10.2 mph</b>
Ground Pressure (Rubber)	<b>5.5 psi</b>

### ▼ Capacities

	<b>T64</b>
Fuel Tank	<b>28.3 gal</b>

## ▼ Hydraulic System

T64

System Relief @ Quick Couplers **3450 psi**

Auxiliary Std Flow **17.6 gpm**

Auxiliary High Flow **26.9 gpm**

## ▼ Dimensions

T64

Ground Pressure (Standard Tracks) **5.5 psi**

Length with Standard Bucket **134.9 in**

Length without Attachment **107 in**

Overall Width **67.8 in**

Overall Height **80.5 in**

Height to Hinge Pin **120 in**

Reach @ Maximum Height **36.7 in**

Turning Radius **81.5 in**

Length of track on ground **72.3 in**

Track Width **12.6 in**

Track Width - Optional **15.7 in**

## ▼ Features

T64

Joystick Control	<b>Optional</b>
Air Conditioning	<b>Optional</b>
Backup Alarm	<b>Standard</b>
BICS System (Interlock)	<b>Standard</b>
Cab Enclosure	<b>Optional</b>
ROPS-Step	<b>N/A</b>
Sound Option	<b>Optional</b>
Cab Heater	<b>Optional</b>
Heater Air Conditioning	<b>Optional</b>
Operating Lights	<b>Standard</b>
Work Lights	<b>Standard</b>
Radio	<b>Optional</b>
Turbocharged Engine	<b>Standard</b>
Rear Window	<b>Standard</b>
Top Window	<b>Standard</b>
Lift-Arm Support	<b>Standard</b>
Grab Handles	<b>N/A</b>
Seat Belt	<b>Standard 2-Point Lap Belt and Optional 3-Point Shoulder Belt on Two-Speed Models</b>
Suspension Seat	<b>Standard</b>

Two Speed Travel	<b>Optional</b>
Deluxe Instrumentation	<b>Optional</b>
Lockable Ignition	<b>N/A</b>
Engine Shutdown	<b>Standard</b>
Hydraulic Bucket Positioning	<b>Optional</b>
High Flow Option	<b>Optional</b>
Auxiliary Hydraulics	<b>Standard</b>
3-Spool Valve	<b>N/A</b>
Spark Arrestor Muffler	<b>DOC</b>
Bob-Tach Attachment System	<b>Standard</b>
Power Bob-Tach	<b>Optional</b>
Ride Control	<b>Optional</b>
Rear Hydraulics	<b>Optional</b>
Horn	<b>Standard</b>